

# LUGGED/TAPPED BUTTERFLY VALVE

Lugged and tapped pattern butterfly valve ideal for pipeline isolation and modulation. Suitable for clean water applications up to 90°C.



## FEATURES

- EN593 Compliant
- Replaceable liner
- Various disc materials
- Install between PN6/10/16 flanges
- Face to face according to EN558 Basic Series 20
- WRAS approved
- Suitable for end of line duty
- Larger sizes on request
- Notched level, handwheel gearbox or actuated operation

## MATERIAL SPECIFICATION

DESCRIPTION	MATERIAL	SPECIFICATION
Body	Cast Iron	EN-GJL-400
Disc	Stainless Steel	AISI 316
Liner	EPDM	
Stem	Stainless Steel	AISI 316
Bearing	PTFE	
Coating	Fushion Bonded Epoxy Resin	

## DIMENSIONAL DRAWINGS

DN	A	B	C	PFA (Bar)	Weight (kg)
40	130	57	32	16	3
50	136	62	43	16	4
65	145	70	46	16	4
80	151	89	46	16	5
100	175	107	52	16	7
150	203	150	56	16	11
200	245	179	60	10	22
250	271	212	68	10	28
300	296	244	77	10	38

Dimensions in mm, unless otherwise stated. DN = Nominal Valve Size.  
PFA = Allowable Operating Pressure

